

# Steel Electric Pallet Truck with Scale 25 In. x 47 In. 3,000 Lb. Capacity

**MODEL EPT-2547-30-SCL-AGM**

Ergonomic Solutions / Electric Pallet Trucks with Scale



## PRODUCT OVERVIEW

The electric pallet truck with scale can verify inbound and outbound freight right on your pallet truck and then move your loads with ease. The LCD scale and function keys (zero, tare, net/gross, print, LB/KG), displays weight in 1 pound increments within trucks rated capacity. The scale display operates on standard alkaline batteries (best accuracy is 0.01 percent of maximum calibrated weight). The scale is not NTEP approved (not legal for trade). Scale head includes RS232 port for serial printing. An individual can raise and lower loads with a push of a button. The unit makes it easy to maneuver loads in warehouses and trailers. Reinforced welded forks with adjustable tie-rods provide long service. The high torque DC drive and lift motor handles...

## KEY FEATURES

- Fully-powered pallet truck makes movement of pallets quick and easy
- Includes fingertip raise and lower buttons for operator convenience
- Safety belly reverse button improves worker safety
- Easy-to-operate throttle for forward and reverse direction

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**662 lbs**

ASSEMBLED SIZE  
**49" W x 66" L x 28.5" H**

SHIP WEIGHT  
**702 lbs**

PACKAGE 1 SIZE  
**42" W x 85" D x 57" H**

COLOR / FINISH  
**Black / Yellow**

FREIGHT TYPE  
**LTL Palletized**

**AVAILABILITY** Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                      |                                  |
|--------------------------------------|----------------------------------|
| Uniform Capacity (lb.)               | 3,000                            |
| Service Range (in.)                  | 3-3/8 to 8                       |
| Fork Width x Length (in.)            | 6-11/16 x 48                     |
| Fork Spacing (in.)                   | 25-9/16                          |
| Drive Wheel Width/Diameter (in.)     | 3-1/8 x 10                       |
| Load Roller Width/Diameter (in.)     | 3 x 2-3/4                        |
| Turn Radius (in.)                    | 52                               |
| Battery Charger                      | 120V Input, 24V/10 amp           |
| Battery Qty./Type                    | (2) 12V AGM (Absorbed Glass Mat) |
| Drive Motor KW                       | 0.7                              |
| Lift Motor KW                        | 1.3                              |
| Operation Time with Full Charge      | 3 to 4 hours                     |
| Operation Time with Intermittent Use | 8 hours                          |
| Battery Depth                        | 11                               |
| Battery Width                        | 14                               |
| Battery Height                       | 10                               |
| Battery Weight                       | 98                               |
| Battery Freight Class                | 60                               |
| Battery NMFC Number                  | 60700                            |
| Battery NMFC Description             | Gel batteries on unit            |
| Lithium Battery Configuration        | C -- Contained In                |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=343>