

# Steel Floor Lock 6-9/16 to 7-5/8 In. Height Silver

**MODEL FL-LKH-6**

Facilities Maintenance / Polyurethane Floor Locks

## PRODUCT OVERVIEW

Floor locks are ideal for maintenance and construction facilities. The unit is designed to create a stable environment, while decreasing the chance of jostling or slight movement. The unit is constructed of steel with a thermoplastic polyurethane base. To use, place the unit close to a desired wheel or caster and raise until tension is built. Once secured, a simple locking device can be activated by applying pressure to the foot pedal.

## KEY FEATURES

- Steel construction for durability
- Thermoplastic polyurethane base for stability
- Locking device for quick service
- Lightweight for portability

## CORE PRODUCT DATA

|                                                                                                                                                 |                                                               |                                      |
|-------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|--------------------------------------|
| <b>ASSEMBLED WEIGHT</b><br><b>5 lbs</b>                                                                                                         | <b>ASSEMBLED SIZE</b><br><b>6.5625" W x 7.625" L x 4.5" H</b> | <b>SHIP WEIGHT</b><br><b>5 lbs</b>   |
| <b>PACKAGE 1 SIZE</b><br><b>6" W x 8" D x 6" H</b>                                                                                              | <b>COLOR / FINISH</b><br><b>Silver</b>                        | <b>FREIGHT TYPE</b><br><b>Parcel</b> |
| <b>AVAILABILITY</b> Available<br>Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering. |                                                               | <b>QUICKSHIP: YES</b>                |

PRODUCT SPECIFICATIONS

|                                          |                                  |
|------------------------------------------|----------------------------------|
| Lowered Height (in.)                     | 6-9/16                           |
| Raised Height (in.)                      | 7-5/8                            |
| Foot Pad Diameter (in.)                  | 3-5/16                           |
| Foot Pad Material                        | Thermoplastic polyurethane (TPU) |
| Grip Pedal Material                      | Thermoplastic polyurethane (TPU) |
| Mounting Plate (in.)                     | 3-15/16 x 4-1/2                  |
| Slotted Holes on Center (in.)            | 3-1/16, 3-11/16                  |
| Mounting Plate Thickness (in.)           | 3/16                             |
| Slotted Mounting Hole Width/Height (in.) | 3/8 x 13/16                      |
| Inside Bolt Hole Spacing (in.)           | 2-9/16 X 3-3/16                  |
| Outside Bolt Hole Spacing (in.)          | 3-3/16 X 3-11/16                 |
| Suggested Caster Size (in.)              | 6                                |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1067>