

Steel Multi Station Jib Crane 120 In. I-Beam 1000 Lb. Capacity Blue

MODEL JIB-P-10-10-10

Overhead Lifting / Multi-Station Transportable Jib Cranes

PRODUCT OVERVIEW

A multi-station transportable Jib crane is designed for use in multiple locations, includes jib crane and one base socket. Extra base sockets may be purchased for use in other locations. Friction brake design allows positive locking and controlled rotation of heavy loads. Standard six (6) inch high I-beam with three (4) inch flange width. Rugged welded steel construction. Requires reinforced concrete pad for installation. Hoist and trolley sold separately.

KEY FEATURES

- Six (6) inch high I-beam with four (4) inch flange width
- Hand operated manual brake
- Arm manually rotates 360 degrees for maximum versatility
- Rugged welded steel construction provides long lasting use

CORE PRODUCT DATA

ASSEMBLED WEIGHT
579 lbs

ASSEMBLED SIZE
132.6875" W x 135.375" L x 17" H

SHIP WEIGHT
640 lbs

PACKAGE 1 SIZE
29" W x 144" D x 24" H

COLOR / FINISH
Blue

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	1,000
Overall I-Beam Span (in.)	120
I-Beam (Flange x Height) (in.)	4 x 6
Rotation Degree	360
Mounting Plate Width/Length (in.)	17 x 17
Boom Reach (in.)	115-3/4
Usable Boom Height (in.)	119-13/16
Nominal Pipe Size [NPS] (in.)	8
Pipe Outside Diameter [OD] (in.)	8-5/8
Pipe Wall Thickness (in.)	21/64
Pipe Inside Diameter [ID] (in.)	7-31/32
Pipe Material	ASTM A53 Steel
Pipe Material Schedule	40
Overall Length (in.)	135-3/8
Overall Height (in.)	132-11/16
Overall Width (in.)	17

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=533>