

# Steel Orbit Non Telescoping Lift Boom 24 In. Fork Pocket Center 4,000 Lb. Capacity Blue

**MODEL LM-OBNT-4-24**

Fork Truck Attachments / Orbiting Fork Truck Booms

## PRODUCT OVERVIEW

The non-telescoping orbit lift boom delivers heavy-duty performance, maximum operator convenience, and uncompromising safety in challenging manufacturing and warehouse environments. Fabricated from high-strength structural steel and welded to rigorous AWS standards, this rugged, durable unit is engineered for years of reliable, long-term service. For precision operation, it features a locking detent and safety restraint that secures the boom directly to the fork truck to ensure secure, slip-free performance. Ready for immediate use, each unit comes fully equipped with two high-capacity lifting hooks to maximize your facility's material handling efficiency.

## KEY FEATURES

- Unique design converts fork trucks into overhead lifting cranes
- Fork pockets with safety strap attach & secure boom to fork truck
- Robotically welded construction provides precision and durability
- Operations & capacity sticker provide user instructions and safety

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**337 lbs**

ASSEMBLED SIZE  
**26.625" W x 80.875" L x 32" H**

SHIP WEIGHT  
**337 lbs**

PACKAGE 1 SIZE  
**32" W x 83" D x 27" H**

COLOR / FINISH  
**Blue**

FREIGHT TYPE  
**LTL Loose**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                   |                 |
|-----------------------------------|-----------------|
| Uniform Capacity (lb.)            | 4,000           |
| Fork Pocket Center (in.)          | 24              |
| Fork Pocket Size (in.)            | 7-1/2 x 2-1/2   |
| Restraint Length (in.)            | 36              |
| Boom Style                        | Non-Telescoping |
| Minimum/Maximum Hook Point (in.)  | 36/78           |
| Single-Hook Capacity at 36" (lb.) | 4,000           |
| Single-Hook Capacity at 48" (lb.) | 3,750           |
| Single-Hook Capacity at 60" (lb.) | 3,500           |
| Single-Hook Capacity at 72" (lb.) | 3,250           |
| Single-Hook Capacity at 78" (lb.) | 3,000           |
| Overall Max Tilted Height (in.)   | 57-3/16         |
| Retracted Hook Height (in.)       | 5-1/2           |
| Max Tilted Hook Height (in.)      | 38-1/4          |
| Maximum Tilt Degree               | 37              |
| Boom Type                         | Orbit Boom      |
| OSHA                              | 1910.178(a)(4)  |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1775>