

# Steel Orbit Non Telescoping Lift Boom 24 In. Fork Pocket Center 8,000 Lb. Capacity Blue

**MODEL LM-OBNT-8-24**

Fork Truck Attachments / Orbiting Fork Truck Booms

## PRODUCT OVERVIEW

The non-telescoping orbit lift boom delivers heavy-duty performance, maximum operator convenience, and uncompromising safety in challenging manufacturing and warehouse environments. Fabricated from high-strength structural steel and welded to rigorous AWS standards, this rugged, durable unit is engineered for years of reliable, long-term service. For precision operation, it features a locking detent and safety restraint that secures the boom directly to the fork truck to ensure secure, slip-free performance. Ready for immediate use, each unit comes fully equipped with two high-capacity lifting hooks to maximize your facility's material handling efficiency.

## KEY FEATURES

- Unique design converts fork trucks into overhead lifting cranes
- Fork pockets with safety strap attach & secure boom to fork truck
- Robotically welded construction provides precision and durability
- Operations & capacity sticker provide user instructions and safety

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**490 lbs**

**ASSEMBLED SIZE**  
**25.125" W x 79.5" L x 32" H**

**SHIP WEIGHT**  
**792 lbs**

**PACKAGE 1 SIZE**  
**32" W x 89" D x 29" H**

**COLOR / FINISH**  
**Blue**

**FREIGHT TYPE**  
**LTL Loose**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                   |                 |
|-----------------------------------|-----------------|
| Uniform Capacity (lb.)            | 8,000           |
| Fork Pocket Center (in.)          | 24              |
| Fork Pocket Width (in.)           | 7-1/4 x 2-1/4   |
| Restraint Length (in.)            | 36              |
| Boom Style                        | Non-Telescoping |
| Minimum/Maximum Hook Point (in.)  | 36/78           |
| Single-Hook Capacity at 36" (lb.) | 8000            |
| Single-Hook Capacity at 48" (lb.) | 6650            |
| Single-Hook Capacity at 60" (lb.) | 6000            |
| Single-Hook Capacity at 72" (lb.) | 5300            |
| Single-Hook Capacity at 78" (lb.) | 4850            |
| Overall Extended Height (in.)     | 57-3/16         |
| Retracted Hook Height (in.)       | 4-11/16         |
| Extended Hook Height (in.)        | 40-3/8          |
| Maximum Tilt Degree               | 37              |
| Boom Type                         | Orbit Boom      |
| OSHA                              | 1910.178(a)(4)  |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1775>