

Steel Two Speed Commercial Direct Driver Blower 39 In. x 13 In. x 40 In. Black

MODEL MB-RS-C-36

Facilities Maintenance / Commercial Direct Drive Blowers

PRODUCT OVERVIEW

The commercial direct drive stationary blower works well in industrial settings. has a two speed, ball bearing motor that is permanently lubricated. The blower does not have a totally enclosed motor.

KEY FEATURES

- Enclosed wire front
- 3 blade design
- Meets OSHA standards and is UL listed
- Wheels included for quick movement



CORE PRODUCT DATA

ASSEMBLED WEIGHT
70 lbs

ASSEMBLED SIZE
40" W x 39" L x 13" H

SHIP WEIGHT
70 lbs

PACKAGE 1 SIZE
40" W x 40" D x 12" H

COLOR / FINISH
Black

FREIGHT TYPE
Parcel

AVAILABILITY Quote Required - Please Contact Sales

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Blade Diameter (in.)	36
Amps High	3.6
CFM High	8200
CFM Low	7,000
Type	Stationary
Conductor Cord Length (in.)	72
Conductor Cord	SJT type 3
Motor Horsepower	1/3
Voltage/Phase	115V/1PH

PRODUCT & SHIPPING REFERENCE

Shipping Point: Louisville, KY 40213

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES

See the live product page for current documents and downloads.



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=125>