

Steel Adjustable Powered Lift Stacker 62 In. Raised Height 2,000 Lb. Capacity Black / Yellow

MODEL S-62-AA

Ergonomic Solutions / Stackers with Powered Drive and Powered Lift



PRODUCT OVERVIEW

The stacker with powered drive and powered lift is a fully powered electric stacker that transports loads throughout warehouse facilities quickly and with less effort. The high torque drive and lift motor handles heavy-duty jobs. The ergonomic handle features easy-to-operate throttle with infinite adjustment of forward and reverse speeds, lift/lower controls, proprietary safety-enhancing emergency reverse function, and horn. When the proprietary safety-enhancing emergency reverse function is actuated, the emergency reverse belly switch instantly reverses direction and moves the unit forward (away from the operator) until the switch is released or after five seconds have elapsed. The built-in safety circuit will automatically disable the entire unit...

KEY FEATURES

- Fully-powered pallet truck makes movement of pallets quick and easy
- Includes fingertip raise and lower buttons for operator convenience
- Safety belly reverse button improves worker safety
- Easy-to-operate throttle for forward and reverse direction

CORE PRODUCT DATA

ASSEMBLED WEIGHT
990 lbs

ASSEMBLED SIZE
82.6875" W x 69" L x 58" H

SHIP WEIGHT
1306 lbs

PACKAGE 1 SIZE
65" W x 81" D x 84" H

COLOR / FINISH
Black / Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	2,000
Service Range (in.)	2-1/8 to 62
Fork Width/Length (in.)	4 x 42
Adjustable Fork Spacing (in.)	8 to 26-3/4 (OD)
Adjustable Leg Spacing (in.)	38-3/16 to 50 (ID)
Overall Mast Height (in.)	78
Drive Motor	DC 24V / 0.7 KW
Lift Motor	DC 24V / 2.0 KW
Battery	(2) 12V / 95 Ah
Battery Charger	DC 24V / 6 amp
Operation Time with Constant Use (hrs.)	3 to 4
Operation Time with Intermittent Use (hrs.)	8
Drive Wheel Qty./Diameter/Width (in.)	(1) 10 x 3-3/8
Front Wheel Qty./Diameter/Width (in.)	(2) 4 x 2.9
Stabilizer Wheel Qty./Diameter/Width (in.)	(2) 3 x 1.4
Wheel Material	Poly-on-Steel
Travel Speed - Loaded (MPH)	3.1
Travel Speed - Unloaded (MPH)	3.8
Battery Depth	11
Battery Width	14
Battery Height	9
Battery Weight	84
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=252>