

PVC Vinyl Strip Door 2/25 In. Standard Overlap Header Mount 108 In. x 120 In. Clear

MODEL TG-800-S-H-108-120

Loading Dock Equipment / Vinyl Strip Doors



PRODUCT OVERVIEW

Vinyl strip doors help control noise, dust, fumes, and smoke while minimizing drafts, reducing illnesses, and accidents. The strip doors offer visual clarity without sacrificing safety. The material design also deters UV rays during direct sunlight when applied to load docks and external doorways. The simple low cost design is easy to maintain. Standard material design meets USDA requirements and is great for refrigeration applications up to -10 degrees Fahrenheit. All doors are shipped pre-assembled and ready for installation. Installation hardware not included. Custom door sizes and material available, contact factory.

KEY FEATURES

- Vinyl strip design helps to minimize heating and cooling costs
- Clear strips offer visual clarity & employee safety
- Fire resistant vinyl construction is self-extinguishing
- Smooth surface design allows user to comfortably enter & exit

CORE PRODUCT DATA

ASSEMBLED WEIGHT
100 lbs

ASSEMBLED SIZE
120" W x 0.08" L x 108" H

SHIP WEIGHT
140 lbs

PACKAGE 1 SIZE
30" W x 96" D x 28" H

COLOR / FINISH
Clear

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Mounting Design	Header
Overlap Style	Standard
PVC/Vinyl Thickness (in.)	0.08
Strip Width (in.)	8
Opening Width (in.)	108
Opening Height (in.)	120
Tensile Strength (PSI)	2635
Maximum Tensile Elongation (percent)	388
Graves Tear Load (lb.)	35.4
Graves Tear Extension (in.)	2.07
Load at 100% Elongation (lbs.)	32.2
Strength at 100% Elongation (PSI)	1181
Stiffness in Flexure - 23 degrees Celsius (PSI)	1805
Brittleness Temperature by Impact (degrees Celsius)	-35
Recommended Operating Temperature - Range (degrees Celsius)	-10 to 140
Specific Gravity	1.22
Haze Transmittance (percent)	6.30
Luminous Transmittance (percent)	82.80

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=27>