

# Steel AC Powered Jib Crane 3-5 Ft. Boom 2,000 Lb. Capacity Blue

**MODEL WTJ-20-3-AC**

Overhead Lifting / Power Lift Jib Cranes



## PRODUCT OVERVIEW

A power lift Jib crane is designed for material handling applications on docks, in warehouses or in truck beds. This intermittent unit uses crane feature rotation hand brakes that offer unlimited positioning. The mast mounts permanently. Boom adjusts in one (1) foot increments and can be positioned at four (4) elevations. Fingertip switch to raise and lower hook. Folds for storage. Unit is designed for vertical lifting only. Do not use unit for lifting personnel or overhead lifting.

## KEY FEATURES

- Powered cable winch makes lifting and maneuvering easy
- Boom telescopes in and out for greater reach and versatility
- 360 Degrees swivel design allows for maximum accessibility
- Pre-drilled base plate makes mounting quick and easy

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**245 lbs**

**ASSEMBLED SIZE**  
**12" W x 53.375" L x 70.0625" H**

**SHIP WEIGHT**  
**280 lbs**

**PACKAGE 1 SIZE**  
**29" W x 66" D x 18" H**

**COLOR / FINISH**  
**Blue**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                              |                   |
|----------------------------------------------|-------------------|
| Uniform Capacity (lb.)                       | 2,000             |
| Boom Reach (in.)                             | 39-1/4 to 63-1/4  |
| Boom Height (in.)                            | 59-9/16 to 96-1/8 |
| Rotation Degree                              | 360               |
| Boom Adjustment Increments (in.)             | 12                |
| Cable Length (ft.)                           | 25                |
| Cable Diameter (in.)                         | 7/32              |
| AC (volts)                                   | 115               |
| Horsepower (HP)                              | 1/3               |
| Mounting Plate Length (in.)                  | 12                |
| Mounting Plate Width (in.)                   | 12                |
| Capacity at 59-9/16" Fully Retracted (lbs.)  | 650               |
| Capacity at 59-9/16" Mid-Position (lbs.)     | 400               |
| Capacity at 59-9/16" Fully Extended (lbs.)   | 250               |
| Capacity at 74-1/4" Fully Retracted (lbs.)   | 1,000             |
| Capacity at 74-1/4" Mid-Position (lbs.)      | 770               |
| Capacity at 74-1/4" Fully Extended (lbs.)    | 600               |
| Capacity at 86-13/16" Fully Retracted (lbs.) | 1,250             |
| Capacity at 86-13/16" Mid-Position (lbs.)    | 950               |
| Capacity at 86-13/16" Fully Extended (lbs.)  | 780               |
| Overall Width (in.)                          | 12                |
| Overall Retracted Length (in.)               | 53-3/8            |
| Overall Height (in.)                         | 70-1/16           |
| Overall Storage Height (in.)                 | 73                |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=582>